



SKU BSQ-240-7X-QD-DR2 Job Name: Mark: Submitted By: Date: 04/17/2025

# Square Centrifugal Inline Fan, Product # BSQ-240-7X-QD-DR2, 4198-6741 CFM




Model BSQ centrifugal inline fan features a unique combination of installation flexibility, rugged construction, ease of service, high efficiency and low sound levels. These compact fans are the ideal selection for indoor clean air applications including intake, exhaust, return or make-up air.


- 34.875 x 34.875 inch inlet width x height
- 34.875 x 34.875 inch outlet width x height
- Horizontal or vertical mounting

#### Certifications

AMCA Sound & Air UL/cUL 705



# **Performance Characteristics**



#### **Construction Features**

Housing Material	Galvanized Steel				
Drive Type	Belt Drive				
Impeller Type	Centrifugal Wheel				
Impeller Material	Aluminum				
	Motor cover				
Includes	Unassembled drive				
	package				
Certifications	AMCA Sound & Air				
	UL/cUL 705				
Drive Reckage Description	Motor and drives shipped				
Drive Package Description	loose				

#### Motor Information

Motor Insulation	В				
Motor Phase	1				
Motor Type	NEMA				
Service Factor	1.25				
Voltage	115/208-230				
HP	3/4				
Hertz	60				
Motor Enclosure	Open Drip Proof				
RPM	1800				
Thermal Protection	AutoOverload				
Nominal Efficiency	70.1				
NEMA Frame Size	56				

### Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75
3/4 0.8		0.89 680 550		CFM	6,741	6,433	6,091	5,719	5,317	4,847	4,198
	0.89		550	Sones	15.3	15.1	14.7	14.2	13.7	13	12.4



- Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.
- Performance certified is for installation type B: Free inlet, Ducted outlet.
- Power rating (BHP/kW) includes transmission losses.
- Performance ratings do not include the effects of appurtenances (accessories).
- The inlet sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type B: free inlet hemispherical sone levels.

# California Residents

# ▲ WARNING

This product can expose you to chemicals including cadmium used in the processing of corrosion resistant metal and fasteners, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information visit www.P65Warnings.ca.gov